


REMARKS

The specification has been amended to provide a cross-reference to the previously filed International Application. The Abstract has also been amended to correct typographical errors. Minor, non-narrowing, amendments have been made to certain claims to place these claims in better form for U.S. practice. No new matter has been added.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. § 1.16 or under 37 C.F.R. § 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

By  #49439

for Michael K. Mutter, #29,680

P.O. Box 747
Falls Church, VA 22040-0747
(703) 205-8000

MKM/cqc
0787-0117P

(Rev. 02/12/01)

Attachment: Version with Markings to Show Changes Made

09869859-070601

VERSION WITH MARKINGS TO SHOW CHANGES MADE

The specification has been amended to provide cross-referencing to the International Application.

A new Abstract has been provided.

The claims have been amended as follows:

1. (Twice Amended) Apparatus for the encoding of relative position comprising a first substrate having a first plurality of light transmitting and light blocking regions forming in aggregate a first object pattern of juxtaposed stripes in an object plane; a second substrate positioned relative to and/or spaced from said first substrate; first convergent means fixed to said second substrate for substantially collimating in a first orthogonal plane, being orthogonal to said object plane, light from points of said first object pattern to reimage said light plane corresponding to said first object pattern; and first image detection means positioned at said first image plane for capturing a first image portion comprising a portion of said first image pattern, [characterized in that] wherein said first image portion, corresponding to said juxtaposed stripes, has alternating and juxtaposed light and dark regions the widths, by determination in use of at least one thereof, and sequence of which unambiguously define the location of said first image portion within said first image pattern along a first image axis corresponding to a first object axis at said first object pattern

whereby the relative position along said first object axis of the first substrate relative to the second substrate is determined.

12. (Amended) Apparatus as claimed in [any preceding claim]claim 1 in which at least one of the image detection means comprises a linear CCD array.

14. (Twice Amended) A method for encoding the position of a first substrate relative to a second substrate which comprises the steps of forming a first object pattern in an object plane by providing a first plurality of light transmitting and light blocking regions in the form of juxtaposed stripes on said first substrate; providing first convergent means fixed to said second substrate and positioning said second substrate relative to and/or spaced from said first substrate; substantially collimating with said first convergent means in a first orthogonal plane light from points of said first object pattern and reimaging said light in a first image plane to form a first image pattern at said first image plane corresponding to said first object pattern; positioning first image detection means at said first image plane and capturing a first image portion comprising a portion of said first image pattern, said method comprising [characterised by] determining, by means of the capturing step, the widths and sequence of light and dark regions within the first image portion and unambiguously defining, thereby, the location of said first image portion within said first image pattern along a first image axis corresponding to a

09569859.070601

